## INORGANIC COMPOUND SACCHARIDE COMPOSITION, VEHICLE, RAPIDLY DISINTEGRATING COMPRESSION MOLDED PRODUCT. AND THEIR PRODUCTION

JP2000086537 Patent Number: Publication date: 2000-03-28

Inventor(s):

YOKOI SHINICHIRO; SHISHIDO TAKESHI; TANAKA NOBUKAZU; HOTTA

YOSHIHARU; CHO KIYOAKI; IKUSHIMA HEIJI

Applicant(s):

FUJI CHEM IND CO LTD

Requested

Patent: JP2000086537

Application

Number:

JP19980258946 19980911

**Priority Number** 

(s): **IPC** 

Classification:

A61K47/36

EC Classification:

Equivalents:

## **Abstract**

PROBLEM TO BE SOLVED: To obtain, by spray drying a homogeneous suspension of an inorganic compound and a saccharide, an inorganic compound saccharide composition which has high fluidity and compression moldability in powder, rapidly disintegrating and/or dissolving properties when added into mouse or water in granule or tablet, and strength which does not allow disintegration during production and

SOLUTION: This composition is obtained by spray drying a homogeneous suspension of (A) an inorganic compound (preferably, magnesium methasilicate aluminate, synthetic hydrotalcite, dry aluminum hydroxide gel, precipitated calcium carbonate, magnesium silicate aluminate, magnesium silicate, or the like) and (B) a saccharide (preferably, erythritol, mannitol, sorbitol, xylitol, or the like). It is preferable that the composition contains components A and B at 0.5-99.5 wt.% and 0.5-99.5 wt.%, respectively. It is preferable that the particle size of the composition is 500 &mu m or smaller.

Data supplied from the esp@cenet database - I2